

**MICHIGAN UNIFORM ENERGY CODE COMPLIANCE FORM**  
*Part 10 of the State Construction Code*  
*R408.31061 ET.SEQ*

**JOB ADDRESS:** \_\_\_\_\_ **MUNICIPALITY:** \_\_\_\_\_

**BUILDER:** \_\_\_\_\_ **SUBMITTED BY:** \_\_\_\_\_

**BUSINESS PHONE:** \_\_\_\_\_

**Check Method of Compliance:** Prescriptive: \_\_\_\_\_ Systems Approach: \_\_\_\_\_

**NOTE:** Systems Approach method requires an energy analysis comparison report (ARF 1086.3)

1. Gross area of exterior walls in square feet: \_\_\_\_\_
2. Square feet of fenestration openings: \_\_\_\_\_
3. Percent of fenestration exterior wall opening: \_\_\_\_\_
4. If fenestration openings exceed 20% of gross exterior wall area, indicate the specific trade-off option that will be used for compliance. (R408.31083) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

5. Indicate the percentage of exposed basement wall area (sq. ft. of exposed basement wall divided by sq. ft. of gross area of exterior wall) \_\_\_\_\_

6. Indicate the R-value and type of insulation proposed for use on basement walls to bring exposure down to 7% of the gross area of exterior walls (R408.31081) \_\_\_\_\_

7. Attach documentation for certified or labeled R-values of all pre-manufactured fenestration products including windows, doors and skylights. ( R408.31071)

8. Indicate the proposed insulation R-value for each component.

Walls: \_\_\_\_\_ Slab on grade floors: \_\_\_\_\_ Floors over unconditioned space: \_\_\_\_\_  
(R408.31074) R408.31078) (R408.31077)

Ceiling/Roof: \_\_\_\_\_ Crawl space walls: \_\_\_\_\_  
(R408.31076) (R408.31079)

9. I agree that at the time of inspection, the insulation installer shall provide a certificate for any blown-in or sprayed insulation that lists the following information:
  - a. The initial thickness
  - b. The settled thickness
  - c. The coverage area
  - d. The number of bags used

Signature \_\_\_\_\_ Date \_\_\_\_\_