

SPECIFICATIONS AND CONDITIONS FOR HIGHWAY PERMITS

Effective September 1, 2006

- 1. Definition of Terms:** Whenever the term City is used in the following specifications it shall mean the City of Kentwood, its employees and officials. The term Engineer shall mean the City of Kentwood Engineer or his authorized representatives. The term Contractor shall refer to the person, firm or corporation undertaking the execution of the work under the terms of the permit.
- 2. Bonds and Insurance:** Surety Company Bonds in the amount of \$20,000.00 conditioned upon performance of the conditions of the permit and these specifications and compliance with all requirements of the law shall be filed with the City each year by contractors desiring to obtain highway permits through the year. Also, a certificate of insurance in the amount of \$200,000.00-\$500,000.00 public liability and \$100,000.00 property damage protecting the City of Kentwood against any and all claims for damages arising from operations covered by the permit shall be filed with the City each year.
- 3. Additional Permits:** When the work involved is in connection with any sewer or water system, this permit is issued contingent on the contractor obtaining the necessary permit from the authorities in control of the system for making the proposed extensions and additions.
- 4. Traffic Protection:** The contractor shall provide, erect, and maintain all necessary barricades, lights, warning signs and flagmen to properly safeguard traffic while this work is in progress. The contractor shall designate a foreman who shall be in responsible charge of the work. The contractor must give the foreman authority to carry out all the provisions contained in these Specifications and Conditions for Highway Permits. If the contractor fails or refuses to carry out these provisions at the time, and in a manner which in the opinion of the Engineer is necessary to protect and direct traffic, or if the contractor cannot be located and notified to do so, the City shall have the right to perform the work and the contractor shall reimburse the City for all charges incurred in the work.
- 5. Interfering Structures:** In case it is necessary to move any building or structure above or below ground within the right-of-way of the highway, the same shall be replaced to the satisfaction of the Engineer. Underground structures damaged by boring shall be repaired or replaced.
- 6. Construction Machinery:** All construction machinery shall be equipped with pneumatic tires when any work is done on blacktop or concrete surfaced pavements.
- 7. Pavement Openings:** Structures shall be placed under pavement by boring and jacking, or cutting through the pavement and using an open trench. Tunneling will not be permitted. Cuts through concrete pavement shall be at right angles to the pavement centerline and shall be made at least six(6) inches wider on each side than the width of the trench with a minimum width of thirty-six(36) inches. Removal of all concrete pavement shall be done only with concrete saw and chisels operated by hand or compressed air. Pavement crushers of any type are prohibited. Openings shall be trimmed in straight lines with right angle corners and vertical edges. When openings are three(3) feet or less from expansion or construction joints, the pavement shall be removed to the joint.
- 8. Crossing Roadbed by Boring and Jacking:** When the pipe is installed by boring and jacking, the leading edge of the pipe must precede the auger by a distance equal to one-half the diameter of the pipe. The method to be used shall be approved by the Engineer before work is started.
- 9. Width of Trenches:** Open trenches shall be not less than two(2) feet wide, plus the diameter of the pipe, at the bottom of the excavation; and the maximum width shall be the diameter of the pipe, plus three(3) feet, or as stated on the permit. The slope of the excavated trench shall not be less than one to one.
- 10. Cribbing:** Cribbing shall be used for all trenches where necessary to protect the road surface adjacent to the trench, for safety to the workmen, to safeguard other structures within the highway, and to prevent property damage.
- 11. Excavated Material:** Excavated material shall be deposited so it will not interfere with moving traffic; and precautions must be taken to prevent excavated material from spilling out onto the traveled portion of the highway by temporary wooden retaining walls or other means approved by the Engineer.
- 12. Backfill within Traveled Way:** Backfilling trenches within the traveled portion of the street or road, that is, between the shoulders or curb lines, shall be done as follows: Material shall be sand, gravel, or sandy gravel and shall be placed in successive layers not more than six(6) inches in depth, loose measure, and each layer shall be thoroughly compacted by mechanical compaction and all backfill subject to check by the Controlled Density Method showing a minimum of ninety-five percent(95%) Proctor. All material excavated from the trench, and not used in the backfill, shall be hauled away.
- 13. Backfill Outside Traveled Way:** Backfilled trenches outside the traveled portion of the highway, that is, between the shoulders or curb and right-of-way lines, shall be done as follows: Material may be sand, gravel, or the material removed from the trench, if not frozen, except across driveways where the materials shall be sand, gravel, or sandy gravel. All backfill shall be placed in successive layers not more than twelve(12) inches in depth, loose measure, and each layer shall be thoroughly compacted by mechanical compaction and all backfill subject to check by the Controlled Density Method showing a minimum of ninety percent(90%) Proctor. Topsoil and sod shall be replaced in all trenches across lawns. All material excavated from the trench, and not used in backfill, shall be hauled away.
- 14. Tree Roots:** When tree roots are removed because of trenching, the top of the trees shall be trimmed sufficiently to balance the loss of roots. This trimming shall be done by the contractor under the direction of the City at the contractor's expense. When tree roots are bored for underground utility installations, the distance shall be one(1) foot for each one(1) inch of trunk diameter.
- 15. Temporary Crossings:** When directed by the Engineer, temporary crossing shall be provided over open trenches; and temporary wearing surface shall be placed over backfilled trenches to keep traffic moving or furnish access to abutting property.
- 16. Replacing Wearing Surface:** Permanent wearing surface of bituminous material approved by the Engineer shall be placed in trenches on all blacktop surfaced roads. The thickness shall be equal to the depth of the original blacktop or three(3) inches, whichever is greater. Permanent wearing surface of seven(7) inches of road gravel approved by the Engineer shall be placed in trenches on all gravel or dirt roads. Permanent wearing surface on concrete surfaced roads shall be new concrete pavement of the same type, thickness, and quality as the original pavement. All permanent wearing surfaces shall be placed by the applicant at his own expense.
- 17. Location of Facilities:** All facilities, both below ground and above ground, shall be located as directed by the City. Pipes shall be placed to a depth that will provide not less than four (4) feet of cover between top of roadway surface and the pipe. If at any time the position of the facility interferes with improvements to the highway, it shall be the responsibility of the applicant to move the facility to a location satisfactory to the City. All such moving shall be done at the expense of the applicant.
- 18. Sidewalks and Driveways:** New sidewalks shall be five (5) feet wide and shall be not less than four (4) inches thick and no less than six (6) through drive approach. Concrete driveway and sidewalk material and construction shall comply with the requirements of the Michigan Department of Transportation current specifications for construction (3,500 psi maximum class design strength (6 sack) – SEC. 601, MDOT STANDARD SPECIFICATIONS FOR CONSTRUCTION.) Contractor shall grade off area on a straight line between finished sidewalk, and shoulder line or curb line; and any excess dirt shall be hauled away. The Engineer will furnish lines and grades for sidewalks.

19. Moving Oversize or Overweight Objects:

A. Oversize, or overweight objects:

- 1. Contractor shall submit an application to the Engineer for approval forty eight (48) hours in advance of the move.
- 2. All moving shall be done on pneumatic tired trucks, trailers, moving dollies, or a combination of them; and the load shall be distributed so that no axle will carry more than legal loading.
- 3. Motive power shall be by pneumatic tired truck or tractor and shall be of sufficient size to handle the load without slipping.
- 4. Moving will not be permitted on Saturdays, Sundays, Holidays, or the day before a Holiday.
- 5. Contractor shall furnish the necessary traffic protection in accordance with Kent County Road Commission requirements before a move is made in the road right-of-way.

B. Oversize and overweight objects:

- 1. Contractor shall submit an application to the Engineer for approval seven(7) days in advance of the move.
- 2. All moving shall be done on pneumatic tired trucks, trailers, moving dollies, or a combination of them.
- 3. Items 3, 4, and 5 above shall also apply.

20. Starting the Work: The Engineer shall be given forty eight (48) hours notice before any of the work governed by this permit is started. Street openings shall not be started on Saturdays, Sundays, Holidays, or the day before a Holiday.

21. Restoration of Highway: The contractor shall carry on his work as here-in specified; and upon completion of the work shall restore the highway to the same condition as before the work started, including sodding, seeding, and mulching.

22. Tree Planting in Road Right-of-Way: Applicant shall submit an application to the Engineer for approval of species and location of trees in the road right-of-way.

23. Copy of Permit: The Foreman in charge of this work shall have a copy of the permit and of the specifications and conditions in his possession at all times.

24. Failure to Obtain Permit: The City reserves the right to double all fees listed hereafter where a contractor performs work in the right-of-way without the proper permits.

25. Plan Approval: Allow up to two (2) weeks for water and sewer projects.

26. Fees: All fees shall be paid at the time of obtaining permit and shall be computed according to the following schedule:

A. Transportation:

Moving oversize, but not overweight objects 12 feet-6 inches wide or less.....	\$ 20.00
Moving oversize, but not overweight objects more than 12 feet-6 inches wide but less than sixteen(16) feet wide	\$ 30.00
Moving oversize, but not overweight objects sixteen(16) feet wide or wider (plus time and material)	\$ 35.00
Moving oversize and overweight objects 12 feet-6 inches wide or less	\$ 20.00
Moving oversize and overweight objects more than 12 feet-6 inches wide but less than sixteen(16) feet wide	\$ 30.00
Moving oversize and overweight objects sixteen(16) feet wide or wider (plus time and material)	\$ 35.00
Extended transportation	\$ 100.00
Annual mobile home(14 feet wide) - up to two approved routes.....	\$ 100.00
Annual mobile home(16 feet wide) - one approved route only.....	\$100.00
House / Structure move (plus time and material).....	\$ 60.00

B. Establishing Grades:

Landscaping – Cut of fill (day light)	\$ 145.00
Sidewalks, minimum charge for 100 lineal feet or less	\$ 145.00
Sidewalks, each additional 50 lineal feet	\$ 30.00

C. Driveways:

Residential driveway	\$ 130.00
Residential driveway and sidewalk up to 100 lineal feet	\$ 145.00
Residential driveway/sidewalk for each additional 50 lineal feet	\$ 30.00
Residential driveway/sidewalk restakings.....	\$ 125.00
Residential gravel driveway	\$ 75.00
Commercial driveway w/o curb and gutter	\$ 125.00
Commercial driveway	\$ 150.00
Commercial driveway, each additional driveway.....	\$ 125.00

D. Underground:

Open cuts -	Base fee of \$300.00 with a \$500.00 Escrow... \$ 800.00
One lane	Time and Materials
Multiple Lanes	Time and materials
Utilities not crossing road	\$ 50.00
Utilities crossing road by boring and jacking	\$ 100.00
Utility Boring	\$50.00 plus \$.40/ft

E. Soil Borings:

Per job minimum.....	\$ 50.00
Over 25 bores	\$ 100.00

F. Miscellaneous:

All permits not listed above	\$ 50.00
------------------------------------	----------